

HUBBELL

Power Systems

Tee Copper Compression

By ANDERSON

Catalog # [BCTCF050C](#)

Copper compression tee for connecting a continuous copper cable to flat pad. Pad holes have NEMA spacing with contact surfaces on both sides.



Features

- Open Run Tee Cable to Flat, 0.813 Main to 3 in, 4 hole Flat Tap
- Material: Copper

General

EU RoHS Indicator	No
Material	Copper
Number of Bolt Holes	4
Number of Ground Braid Lug Holes	0
Number of Pad Holes	4
Type	Tee, Copper Compression
UPC	096359349198

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	5.292 lb
Width - Flat Bar Tap	3 in

Electrical Ratings

Maximum Current Rating Amps Continuous 0

Conductor Related

Conductor Diameter (Main) - Maximum	0.813 in
Conductor Diameter (Main) - Minimum	0.813 in
Conductor Diameter (Main) Range	0.813 - 0.813
Conductor Type	Copper

Product Assets

[Catalogs - Substation Connectors \(SA\)](#)

[Sales Drawings - C-5603 \(BCTCF Product Family\)](#)

[Video - Hubbell Power Systems 3D Portal to help with](#)

[developing 3D models of substation connector products](#)

[Video - Hubbell Power Systems Quick Ship](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
AN-BCTCF050C-SPEC-EN | REV 6/2024