# **HUBBELL Power Systems**

# Cable Spacer, Bronze

By ANDERSON Catalog # BPCS1006

Bronze alloy, parallel cable spacer for maintaining cable clearance and preventing loose cable damage. Recommended for slack spans only.



\*Representative Image

#### **Features**

- Bronze Cable Spacer, 6 in Spacing, range 0.998 1.152 inches (750-1000 MCM)
- Recommended for slack spans only
- Material: Casting bronze alloy, Hardware Stainless Steel

#### General

EU RoHS Indicator No
Material Bronze
Material - Clamping Hardware Stainless Steel

Number of Ground Braid Lug

Holes

Type Cable Spacer UPC 096359292173

#### **Dimensions**

Base Hole Spacing 0 in
Diameter - Base Holes 0 in
Diameter - Bolt 0 in
Diameter - Inside 0 in
Length - Coupling 0 in
Length Before Compression 0 in
Weight 6.468 lb

### **Electrical Ratings**

Maximum Current Rating Amps 0 Continuous

# **Conductor Related**

Conductor Diameter - 1.152 in

Maximum

Conductor Diameter - Minimum 0.998 in Conductor Diameter Range 0.998 - 1.152

Conductor Spacing 6 in
Conductor Type Copper

# Logistics

Pallet Quantity 216

#### **Product Assets**

Catalogs - Substation Connectors (SA)
Sales Drawings - C-12901 (BPCS Product Family)
Video - Hubbell Power Systems 3D Portal to help with
developing 3D models of substation connector products
Video - Hubbell Power Systems Quick Ship

