

# HUBBELL Power Systems

## Suspension Clamp

By ANDERSON  
Catalog # [BRS60C](#)

Bronze suspension clamp for use with copper or copperweld cable. Through the use of these clamps hysteresis and eddy current power losses are reduced to a minimum. Liners are not required.



### Features

- Cable clamping range: 0.20-0.60 in. dia.
- Maximum take-off angle 15 degrees
- Ultimate body strength 16,000 lbs
- C-suffix: adds Clevis-Eye fitting CA04
- The BRS suspension clamp is a saddle type suspension clamp designed for use with copper or Copperweld® cable.

### General

Bolt Installation Torque (Recommended)	480 in-lbs
EU RoHS Indicator	No
Fitting Type	Clevis
Material - Clamp	High Tensile Bronze Alloy
Material - Hardware	Galvanized Steel
Material - Pin	Stainless Steel
Material - Pin (Cotter)	Stainless Steel
Material - Socket and Clevis	Galvanized Ductile Iron
Product Category	Suspension Clamp
Strength Rating - Ultimate	16000 lb
Body	
Type	Ground Wire Suspension Clamps
U-Bolts	1/2 in
UPC	096359349341

### Dimensions

Angle - Take-Off Maximum	15 °
Clamping - Maximum	0.6 in
Clamping - Minimum	0.2 in
Clevis Opening	0.75 in
Diameter - Clevis Pin	0.625 in
Height	2.25 in
Length	6.5 in
Weight	4.5 lb

### Electrical Ratings

Voltage Application	Ground Wire
---------------------	-------------

### Conductor Related

Clamping Range	0.2- 0.6
----------------	----------

### Product Assets

[Catalogs - Transmission Connectors Catalog - Full Literature - Ropes Course Industry Letter \(April 2021\)](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
AN-BRS60C-SPEC-EN | REV 6/2024