

# HUBBELL Power Systems

## Clevis Eye Fitting

By ANDERSON  
Catalog # CA04

Clevis eyes are used to connect conductor clamping devices to clevis tongue insulators. Material: body - galvanized ductile iron, clevis pin - galvanized steel, cotter pin - stainless steel.



\*Representative Image

### Features

- Galvanized ductile iron
- Provided with Clevis Pin & Cotter Pin in clevis

### General

Material	Ductile Iron
Material - Pin (Clevis)	Galvanized Steel
Material - Pin (Cotter)	Stainless Steel
Number of Bolt Holes	0
Series	CA Series
Strength Rating - Ultimate	18000 lb
Strength Rating - Ultimate	0 lb
Body	
UPC	096359296003

### Dimensions

Assembly Rating (Ultimate)	0 lb
Diameter - Bolt	0 in
Diameter - Eye Hole	0.688 in
Diameter - Pin	0 in
Insulator Throat Diameter - Maximum	0 in
Insulator Throat Diameter - Minimum	0 in
Insulator Throat Diameter Range	0 - 0
Length - Coupling	2.5 in
Length - Pin	0 in
Maximum Adjustment	0 in
Ring Height	0 in
Weight	1.215 lb
Width - Eye	0.5 in

### Conductor Related

Conductor Diameter - Maximum	0 in
Conductor Spacing	0 in

### Logistics

Pallet Quantity 1920

### Product Assets

[Catalogs - Transmission Connectors Catalog - Full](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
AN-CA04-SPEC-EN | REV 6/2024