# HUBBELL **Power Systems**

# **Clevis Eye Fitting**

By ANDERSON Catalog # CA1013

Clevis eyes are used to connect conductor clamping devices to clevis tongue insulators. Material: body - galvanized ductile iron, clevis pin - galvanized steel, cotter pin - stainless steel.



\*Representative Image

### **Features**

Galvanized ductile iron

Strength Rating - Ultimate

• Provided with Clevis Pin & Cotter Pin in clevis

# General

Catalog Number	CA1013
EU RoHS Indicator	No
Material	Ductile Iron
Material - Pin (Clevis)	Galvanized Steel
Material - Pin (Cotter)	Stainless Steel
Number of Bolt Holes	0
Series	CA Series
Strength Rating - Ultimate	25000 lb

Body

UPC 096359296065

0 lb

#### **Dimensions**

Maximum

Assembly Rating (Ultimate)	0 lb
Diameter - Bolt	0 in
Diameter - Eye Hole	0.813 in
Diameter - Pin	0 in
Insulator Throat Diameter -	0 in

Insulator Throat Diameter -0 in Minimum Insulator Throat Diameter 0 - 0 Length - Coupling 2.5 in Length - Pin 0 in 0 in Maximum Adjustment Ring Height 0 in 1.96 lb Weight Width - Eye

Conductor Related	
Conductor Diameter -	0 in
Maximum	
Conductor Spacing	0 in

## **Certifications And Compliance**

Buy America(n) Qualified Contact Manufacturer

## Logistics

Pallet Quantity 1200

# **Product Assets**

Catalogs - Transmission Connectors Catalog - Full Specifications - CA1013

