HUBBELL **Power Systems**

Clevis-Clevis Fitting

By ANDERSON Catalog # CCC3090

Clevis Clevises are used to attach clevis tongue insulators to various associated hardware within an insulator string. Material: body - galvanized ductile iron, clevis pin - galvanized steel, cotter pin - stainless steel.

Features

"BNK" suffix if added replaces clevis pin & cotter pin with bolt, nut & cotter pin

General

	Range	
CCC3090	Length - Coupling	3 in
Rotated	Length - Pin	0 in
Ductile Iron	Maximum Adjustment	0 in
Galvanized Steel	Ring Height	0 in
Stainless Steel	Weight	2.45 lb
0		
CCC Series	Conductor Related	
30000 lb	Conductor Diameter -	0 in
0 lb	Maximum	
	Conductor Spacing	0 in
096359297109		
	Logistics	
0 lb	Pallet Quantity	960
0 in	Product Assets	
0 in		
	Rotated Ductile Iron Galvanized Steel Stainless Steel O CCC Series 30000 lb O lb 096359297109 O lb O lb	CCCS050Length - PinRotatedLength - PinDuctile IronMaximum AdjustmentGalvanized SteelRing HeightStainless SteelWeightOConductor RelatedCCC SeriesConductor Diameter - MaximumO lbConductor Spacing096359297109LogisticsPallet QuantityO lbO lbProduct Assets

Catalogs - Transmission Connectors Catalog - Full Specifications - CCC3090



0 in

0 in

0 - 0

Insulator Throat Diameter -

Insulator Throat Diameter -

Insulator Throat Diameter

Maximum

Minimum

Range

