HUBBELL Power Systems

Clevis-Clevis Fitting

By ANDERSON Catalog # CCC309055

Clevis Clevises are used to attach clevis tongue insulators to various associated hardware within an insulator string. Material: body - galvanized ductile iron, clevis pin - galvanized steel, cotter pin - stainless steel.



"BNK" suffix if added replaces clevis pin & cotter pin with bolt, nut & cotter pin

General

Catalog Number CCC309055
Coupling Orientation Rotated
EU RoHS Indicator No
Material Ductile Iron
Material - Pin (Clevis) Galvanized Steel
Material - Pin (Cotter) Stainless Steel

Number of Bolt Holes 0
Series C

Series CCC Series
Strength Rating - Ultimate 30000 lb
Strength Rating - Ultimate 0 lb

Body

UPC 096359297116

Dimensions

Assembly Rating (Ultimate) 0 lb
Diameter - Bolt 0 in
Diameter - Pin 0 in
Insulator Throat Diameter - 0 in

Maximum



Insulator Throat Diameter -0 in Minimum Insulator Throat Diameter 0 - 0 Range Length - Coupling 5.5 in Length - Pin 0 in Maximum Adjustment 0 in Ring Height 0 in Weight 5.586 lb

Conductor Related

Conductor Diameter - 0 in

Maximum

Conductor Spacing 0 in

Certifications And Compliance

Buy America(n) Qualified Contact Manufacturer

Logistics

Pallet Quantity 320

Product Assets

Catalogs - Transmission Connectors Catalog - Full Specifications - CCC309055

