

HUBBELL Power Systems

Corona-Free Clevis-Clevis

By ANDERSON
Catalog # [CFCC3090](#)

Corona free clevis clevises are used at EHV levels to attach clevis tongue insulators to various associated hardware within an insulator string. Material: body - galvanized ductile iron, clevis pin - galvanized steel, cotter pin - stainless steel.



*Representative Image

Features

"Material: Body-Galvanized Ductile iron, Clevis Pin-Galvanized steel, Cotter Pin-Stainless Steel"

General

Coupling Orientation	Rotated
EU RoHS Indicator	No
Material	Ductile Iron
Material - Pin (Clevis)	Galvanized Steel
Material - Pin (Cotter)	Stainless Steel
Number of Bolt Holes	0
Series	CFCC Series
Strength Rating - Ultimate	30000 lb
Strength Rating - Ultimate Body	0 lb
UPC	096359349655

Dimensions

Assembly Rating (Ultimate)	0 lb
Diameter - Bolt	0 in
Diameter - Pin	0 in
Insulator Throat Diameter - Maximum	0 in
Insulator Throat Diameter - Minimum	0 in
Insulator Throat Diameter Range	0 - 0
Length - Coupling	3.125 in
Length - Pin	0 in
Maximum Adjustment	0 in
Ring Height	0 in
Weight	2.94 lb

Conductor Related

Conductor Diameter - Maximum	0 in
Conductor Spacing	0 in

Logistics

Pallet Quantity 720

Product Assets

[Catalogs - Transmission Connectors Catalog - Full](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
AN-CFCC3090-SPEC-EN | REV 6/2024