

Stud Connector, Bronze

By ANDERSON  
Catalog # [D2S0605016](#)

Bronze alloy stud connector for connecting two copper cables or tubes to equipment stud. A wide range of cable or a limited range of tubing may accommodate straight or 90 degree connections. Clamping bolts have hex-stops for one-wrench installation.

Features

- "To specify 90 degree connector, insert "90" into catalog number. Example: DSC0602590163
- All sizes furnished with reversible cable caps"

General

Catalog Number	D2S0605016
EU RoHS Indicator	No
Material	Bronze
Material - Clamping Hardware	Stainless & Galvanized Steel
Number of Ground Braid Lug Holes	0
Number of Stud Threads	16
Type	Stud to Tube or Cable
UPC	096359357018

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Diameter - Stud	3.75 in
Length - Coupling	0 in
Length Before Compression	0 in



Weight2.842 lb

Electrical Ratings

Maximum Current Rating Amps 0  
Continuous

Conductor Related

Conductor Diameter - Maximum	0.813 in
Conductor Diameter - Minimum	0.162 in
Conductor Diameter Range	0.162 - 0.813
Conductor Type	Copper

Certifications And Compliance

Buy America(n) QualifiedBABA Compliant (All status valid till December 2024)

Product Assets

- [Catalogs - Substation Connectors \(SA\)](#)
- [Sales Drawings - CC-1817 \(D2S Product Family\)](#)
- [Specifications - D2S0605016](#)
- [Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products](#)
- [Video - Hubbell Power Systems Quick Ship](#)