HUBBELL
Power Systems

Deadend, Straight Line. Ductile, Copper, Copperweld, Alumoweld Conductor Range 0.36 - 0.60 in, Fitting: None.

By ANDERSON
Catalog # MDE60N

*Representative Image

Deadend, Straight Line. Ductile, Copper, Copperweld, Alumoweld Conductor Range 0.36 - 0.60 in, Fitting: None.

Features

- For use with copper and CopperWeld phase conductor
- Magnetic induction heating will occur
- For dead ending static wire
- Add "S" for socket OR "C" for clevis fitting

General

Catalog Number	MDE60N
Fitting Type	None
Material	Ductile Iron; Steel
Material - Body	Ductile Iron
Material - Hardware	Galvanized Steel
Material - Keeper	Ductile Iron
Product Category	Straight Line
Strength Rating - Ultimate	8000 lb
Body	
Style	MDE
Type	Bolted
U-Bolts	2 in
UPC	096359321958

Dimensions

Clevis Opening	0.75 in
Diameter - Bolt	0.5 in
Diameter - Pin	0.625 in
Length	8.938 in
Weight	3.8 lb
Width	0.75 in

Electrical Ratings

Voltage Application	Standard

Conductor Related

Conductor Compatibility	ACSR-Turkey-6-6/1;ACSR-Raven-1/0-6/1;ACSR-Quail-2/0-6/1;ACSR-Pigeon-3/0-6/1;AAC-Poppy-1/0-7;AAC-Aster-2/0-7;AAC-Phlox-3/0-7;AAC-Oxlip-4/0-7;AAC-Valerian-250-19;AAC-Laurel-266.8-19;AAAC 6201 Alloy-Azusa-123.3-6/18;AAAC 6201 Alloy-Anaheim-155.4-6/18;AAAC 6201 Alloy-Amherst-195.7-6/18;AAAC 6201 Alloy-Alliance-246.9-6/18
Conductor Diameter - Maximum	0.6
Conductor Diameter - Minimum	0.36
Conductor Diameter Range	0.36 - 0.6

Logistics

Pallet Quantity	480

Product Assets

Catalogs - Distribution Connectors
Literature - Ropes Course Industry Letter (April 2021)
Sales Drawings - C-5212
Specifications - MDE60N

©2024 Hubbell Incorporated. All rights reserved