

# HUBBELL Power Systems

## Spring Bolt

By ANDERSON  
Catalog # [SBA5861725](#)

Spring bolts are typically used to maintain controlled tension within spans of substation strain bus. Associated hardware can be used to connect the assembly to the insulation string.



### Features

- "Material: Spring-Galvanized steel, Eyebolt-Galvanized steel, Bearing Plate-Galvanized ductile iron, Nuts-Galvanized steel, Cotter Pin-stainless steel
- Contact factory for other lengths and variations"

### General

Catalog Number	SBA5861725
EU RoHS Indicator	No
Material	Steel
Material - Bearing Plate	Galvanized Ductile Iron
Material - Eyebolt	Galvanized Steel
Material - Pin (Cotter)	Stainless Steel
Number of Bolt Holes	0
Strength Rating - Ultimate	0 lb
Body	
UPC	096359325000

### Dimensions

Assembly Rating (Ultimate)	0 lb
Diameter - Bolt	0 in
Diameter - Pin	0 in
Insulator Throat Diameter - Maximum	0 in
Insulator Throat Diameter - Minimum	0 in
Insulator Throat Diameter Range	0 - 0
Length - Pin	0 in
Maximum Adjustment	0 in
Ring Height	0 in
Weight	15.043 lb

### Conductor Related

Conductor Diameter - Maximum	0 in
Conductor Spacing	0 in

### Logistics

Pallet Quantity 96

### Product Assets

[Sales Drawings - CC-11975 \(SBA Product Family\)](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
AN-SBA5861725-SPEC-EN | REV 6/2024