

# Tee, Bronze Bolted

By ANDERSON Catalog # TCC4050025

"Bolted Tees, Connecting Tubing Main to Tubing Tap at 15 degrees, Tubing Main-IPS/EHIPS-2", Tubing Tap-IPS/EHIPS-1", Material: Castings- Bronze Alloy, Hardware-Silicon Bronze or Stainless Steel"



\*Representative Image

0.813 in

0.325 in

0.575 in

0.204 in

0.813 in

0.325 in

Copper

756

0.325 - 0.813

0.325 - 0.813

## **Features**

- "Tee for Connecting Copper Cable Main to Copper Cable
- All sizes furnished with reversible cable caps"

General		Conductor Diameter (Main) Range
Material  Material - Clamping Hardware	Bronze Stainless Steel	Conductor Diameter (Tap) - Maximum
Number of Ground Braid Lug Holes	0	Conductor Diameter (Tap) - Minimum
Type UPC	Tee, Bolted 096359330875	Conductor Diameter - Maximum
Dimensions		Conductor Diameter - Minimum
Base Hole Spacing	O in	Conductor Diameter Range

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	1.568 lb

## **Electrical Ratings**

Maximum Current Rating	0
Amps Continuous	

## Pallet Quantity

#### **Product Assets**

Conductor Type

Logistics

**Conductor Related** 

Maximum

Minimum

Conductor Diameter (Main) -

Conductor Diameter (Main) -

Catalogs - Substation Connectors (SA)

Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products (VI05050E0619)

Video - Hubbell Power Systems Quick Ship (VIO5124E1018)