

Tee, Bronze Bolted

By ANDERSON Catalog # TCC8050050

"Bolted Tees, Connecting Tubing Main to Tubing Tap at 15 degrees, Tubing Main-IPS/EHIPS-2-1/2", Tubing Tap-IPS/EHIPS-2", Material: Castings- Bronze Alloy, Hardware-Silicon Bronze or Stainless Steel"



*Representative Image

Conductor Related

Conductor Maximum	Diameter	(Main) -	0.813 in
Conductor Minimum	Diameter	(Main) -	0.325 in
Conductor Range	Diameter	(Main)	0.325 - 0.813
Conductor Maximum	Diameter	(Tap) -	0.813 in
Conductor Minimum	Diameter	(Tap) -	0.325 in
Conductor Maximum	Diameter	-	0.813 in
Conductor Minimum	Diameter	-	0.325 in
Conductor	Diameter	Range	0.325 - 0.813
Conductor	Туре		Copper
Logistics			
Pallet Quar	ntity		504
	_		

Product Assets

Catalogs - Substation Connectors (SA)

Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products (VI05050E0619)

Video - Hubbell Power Systems Quick Ship (VI05124E1018)

Features

- "Tee for Connecting Copper Cable Main to Copper Cable Tap
- All sizes furnished with reversible cable caps"

General

Material Material - Clamping Hardware	Bronze Stainless Steel
Number of Ground Braid Lug Holes	0
Туре	Bolted Tees
UPC	096359330950
Dimonsions	

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Clamping Hardware	0.5 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	3.332 lb

Electrical Ratings

Maximum Current Rating Amps Continuous

HUBBELL

0