

Bronze Bolted Tap Lug Terminal

By ANDERSON  
Catalog # [TLD62LTP](#)



Bronze alloy terminal for connecting one or two copper cables directly to a flat copper pad. Recommended for power or grounding applications. Material: Castings-Bronze alloy, Eyebolt-High strength bronze, Hardware-Stainless steel; For copper cable connection to aluminum bus bar, specify tin-plated terminal with Belleville spring washer by adding suffix TPBW to catalog number.

Features

- "Recommended for power or grounding applications
- can be tandem mounted side by side on NEMA 1-3/4" hole centers drilled for 1/2" bolts
- Tin plating will be supplied"

General

Catalog Number	TLD62LTP
Material	Bronze
Material - Clamping Hardware	Stainless Steel
Number of Ground Braid Lug Holes	0
Type	Tap Lug
UPC	096359331483

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Thickness - Mounting Pad Maximum	0.75 in

Weight1.274 lb

Electrical Ratings

Maximum Current Rating Amps0  
Continuous

Conductor Related

Conductor Diameter - Maximum	0.813 in
Conductor Diameter - Minimum	0.325 in
Conductor Diameter Range	0.325 - 0.813
Conductor Type	Copper

Logistics

Carton Quantity	32
Pallet Quantity	960

Product Assets

[Catalogs - Substation Connectors \(SA\)](#)  
[Specifications - TLD62LTP](#)  
[Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products](#)  
[Video - Hubbell Power Systems Quick Ship](#)