

HUBBELL

Power Systems

Bronze Bolted Tap Lug Terminal

By ANDERSON
Catalog # [TLS22L](#)



Bronze alloy terminal for connecting a copper cable directly to a flat copper pad. Recommended for power or grounding applications. Material: Castings-Bronze alloy, Eyebolt-High strength bronze, Hardware-Stainless steel; For copper cable connection to aluminum bus bar, specify tin-plated terminal with Belleville spring washer by adding suffix TPBW to catalog number.

Features

- "Recommended for power or grounding applications
- Specify tin-plated terminal with Belleville spring washer by adding suffix TPBW to catalog number Example: TLS22LTPBW"

General

Material	Bronze
Material - Clamping Hardware	Stainless Steel
Number of Ground Braid Lug	0
Holes	
Type	Tap Lug
UPC	096359331582

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Dimensions	1.125 in x 1.938 in x 0.875 in
Height	0.875 in
Length	1.125 in
Length - Coupling	0 in
Length Before Compression	0 in
Thickness - Mounting Pad	0.75 in
Maximum	
Weight	0.186 lb
Width	1.938 in

Electrical Ratings

Maximum Current Rating Amps 0
Continuous

Conductor Related

Conductor Diameter - Maximum	0.332 in
Conductor Diameter - Minimum	0.102 in
Conductor Diameter Range	0.102 - 0.332
Conductor Type	Copper

Logistics

Pallet Quantity 6400

Product Assets

[Catalogs - Substation Connectors \(SA\)](#)
[Sales Drawings - TLS Product Family](#)
[Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products](#)
[Video - Hubbell Power Systems Quick Ship](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
AN-TLS22L-SPEC-EN | REV 6/2024