

Bronze Bolted Tap Lug Terminal

By ANDERSON
Catalog # [TLS22L](#)

Bronze alloy terminal for connecting a copper cable directly to a flat copper pad. Recommended for power or grounding applications. Material: Castings-Bronze alloy, Eyebolt-High strength bronze, Hardware-Stainless steel; For copper cable connection to aluminum bus bar, specify tin-plated terminal with Belleville spring washer by adding suffix TPBW to catalog number.

Features


- "Recommended for power or grounding applications
- Specify tin-plated terminal with Belleville spring washer by adding suffix TPBW to catalog number Example: TLS22LTPBW"

General

Catalog Number	TLS22L
Material	Bronze
Material - Clamping Hardware	Stainless Steel
Number of Ground Braid Lug Holes	0
Type	Tap Lug
UPC	096359331582

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Dimensions	1.125 in x 1.938 in x 0.875 in
Height	0.875 in
Length	1.125 in
Length - Coupling	0 in
Length Before Compression	0 in



Thickness - Mounting Pad Maximum	0.75 in
Weight	0.186 lb
Width	1.938 in

Electrical Ratings

Maximum Current Rating Amps Continuous	0
--	---

Conductor Related

Conductor Diameter - Maximum	0.332 in
Conductor Diameter - Minimum	0.102 in
Conductor Diameter Range	0.102 - 0.332
Conductor Type	Copper

Logistics

Pallet Quantity	6400
-----------------	------

Product Assets

- [Catalogs - Substation Connectors \(SA\)](#)
- [Sales Drawings - TLS Product Family](#)
- [Specifications - TLS22L](#)
- [Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products](#)
- [Video - Hubbell Power Systems Quick Ship](#)