

Bronze Bolted Tap Lug Terminal

By ANDERSON
Catalog # [TLS52L](#)



Bronze alloy terminal for connecting a copper cable directly to a flat copper pad. Recommended for power or grounding applications. Material: Castings-Bronze alloy, Eyebolt-High strength bronze, Hardware-Stainless steel; For copper cable connection to aluminum bus bar, specify tin-plated terminal with Belleville spring washer by adding suffix TPBW to catalog number.

Features

- "Recommended for power or grounding applications
- Specify tin-plated terminal with Belleville spring washer by adding suffix TPBW to catalog number Example: TLS52LTPBW"

General

Catalog Number	TLS52L
Material	Bronze
Material - Clamping Hardware	Stainless Steel
Number of Ground Braid Lug Holes	0
Type	Tap Lug
UPC	096359331780

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Dimensions	1.688 in x 2.75 in x 1.313 in
Height	1.313 in
Length	1.688 in
Length - Coupling	0 in
Length Before Compression	0 in
Thickness - Mounting Pad	0.75 in
Maximum Weight	0.463 lb

Width	2.75 in
-------	---------

Electrical Ratings

Maximum Current Rating Amps	0
Continuous	

Conductor Related

Conductor Diameter - Maximum	0.681 in
Conductor Diameter - Minimum	0.258 in
Conductor Diameter Range	0.258 - 0.681
Conductor Type	Copper

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
--------------------------	---

Logistics

Pallet Quantity	2400
-----------------	------

Product Assets

[Catalogs - Substation Connectors \(SA\)](#)
[Sales Drawings - TLS Product Family](#)
[Specifications - TLS52L](#)
[Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products](#)
[Video - Hubbell Power Systems Quick Ship](#)