HUBBELL
Power Systems

Terminal, Compression

By ANDERSON
Catalog # VACL3012

VERSAtile Aluminum Compression Terminal, COMP 3/0 str AL/CU, 1 H, 1/2"

*Representative Image

Features

Rated at 34.5 KV. UL listed for aluminum or copper conductors. CSA certified.

General

Catalog Number	VACL3012
Crimp Method	VERSAtile™ (Accomodates Conventional And Anderson Tools)
Die Size	*See Resources / Downloads for die selection and installation instructions
EU RoHS Indicator	Contact Manufacturer
Material	Aluminum Alloy - Tin Plated
Material - Body	Aluminum
Number of Pad Holes	1
Physical Attribute - Number of Holes	1
Style	Pressed Tubing
UPC	096359334132

Dimensions

Diameter - Pad Bolt	0.5 in
Dimension - Bolt Hole Size inch	0.500 in
Weight	0.098 lb

Conductor Related

Conductor Compatibility	ACSR-Swan-4-6/1;ACSR-Swanate-4-7/1;ACSR-Sparrow-2-6/1;ACSR-Sparate-2-7/1;ACSR-Robin-1-6/1;ACSR-Raven-1/0-6/1;ACSR-Quail-2/0-6/1;AAC-Rose-4-7;AAC-Iris-2-7;AAC-Pansy-1-7;AAC-Poppy-1/0-7;AAC-Aster-2/0-7;AAC-Phlox-3/0-7;AAAC 6201 Alloy-Alton-48.69-6/18;AAAC 6201 Alloy-Ames-77.47-6/18;AAAC 6201 Alloy-Azusa-123.3-6/18;AAAC 6201 Alloy-Anaheim-155.4-6/18
Conductor Diameter (VersaCrimp) - Maximum	0.47 in
Conductor Diameter (VersaCrimp) - Minimum	0.232 in

Certifications And Compliance

UL Listed	Yes

Product Assets

Catalogs - Distribution Connectors
Installation Manuals - VACL Terminal Die Chart
Sales Drawings - VACL Terminal Sales Drawing
Specifications - VACL3012

©2024 Hubbell Incorporated. All rights reserved