

HUBBELL Power Systems

Terminal, Compression

By ANDERSON
Catalog # [VACL414](#)

VERSAtile Aluminum Compression Terminal, #4 str AL/CU, 1 H,
1/4"



*Representative Image

Features

Rated at 34.5 KV. UL listed for aluminum or copper conductors.
CSA certified.

General

Crimp Method	VERSAtile™ (Accommodates Conventional And Anderson Tools)
Die Size	*See Resources / Downloads for die selection and installation instructions
EU RoHS Indicator	Contact Manufacturer
Material	Aluminum Alloy - Tin Plated
Material - Body	Aluminum
Number of Pad Holes	1
Physical Attribute - Number of Holes	1
Style	Pressed Tubing
UPC	096359334217

Dimensions

Diameter - Pad Bolt	0.25 in
Dimension - Bolt Hole Size inch	0.250 in
Weight	0.02 lb

Conductor Related

Conductor Compatibility	AAC-Rose-4-7
Conductor Diameter (VersaCrimp) - Maximum	0.232 in
Conductor Diameter (VersaCrimp) - Minimum	0.232 in

Certifications And Compliance

UL Listed	Yes
-----------	-----

Logistics

Carton Quantity	500
-----------------	-----

Product Assets

[Catalogs - Distribution Connectors](#)
[Installation Manuals - VACL Terminal Die Chart](#)
[Sales Drawings - VACL Terminal Sales Drawing](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
AN-VACL414-SPEC-EN | REV 6/2024