

HUBBELL

Power Systems

Aluminum Compression Terminal for 2/0 AL/CU, 2/0 6/1 ACSR, 3/0 COMPACT

By ANDERSON
Catalog # [VAUL2012](#)

Aluminum Compression Terminal for 2/0 AL/CU, 2/0 6/1 ACSR,
3/0 COMPACT



*Representative Image

Features

Connectors are prefilled with rubber compatible inhibitor and sealed with color coded end caps.

General

Catalog Number	VAUL2012
Color Code	Gray
Crimp Method	VERSAtile™ (Accommodates Conventional And Anderson Tools)
Die Size	*See Resources / Downloads for die selection and installation instructions
EU RoHS Indicator	Contact Manufacturer
Material	Aluminum
Material - Body	Aluminum
Number of Pad Holes	1
Physical Attribute - Number of Holes	1
Plating	No
Style	Impact Extruded
UPC	096359334699

Dimensions

Diameter - Pad Bolt	0.5 in
Dimension - Hole Size inch	0.500 in
Weight	0.196 lb

Conductor Related

Conductor Compatibility	ACSR-Swan-4-6/1;ACSR-Swanate-4-7/1;ACSR-Sparrow-2-6/1;ACSR-Sparate-2-7/1;ACSR-Robin-1-6/1;ACSR-Raven-1/0-6/1;ACSR-Quail-2/0-6/1;AAC-Rose-4-7;AAC-Iris-2-7;AAC-Pansy-1-7;AAC-Poppy-1/0-7;AAC-Aster-2/0-7;AAAC 6201 Alloy-Alton-48.69-6/18;AAAC 6201 Alloy-Ames-77.47-6/18;AAAC 6201 Alloy-Azusa-123.3-6/18
Conductor Diameter (VersaCrimp) - Maximum	0.447 in
Conductor Diameter (VersaCrimp) - Minimum	0.213 in

Certifications And Compliance

UL Listed	No
-----------	----

Logistics

Carton Quantity	100
-----------------	-----

Product Assets

[Catalogs - Distribution Connectors](#)
[Installation Manuals - VAUL Terminals Installation Procedures](#)
[Sales Drawings - VAULxxx_drawing](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
AN-VAUL2012-SPEC-EN | REV 6/2024