

Aluminum Compression Terminal for 300 - 350 AL/CU, 266.8 18/1, 26/7, 336.4 18/1 ACSR, 350 - 400 COMPACT

By ANDERSON
Catalog # [VAUL36012BN](#)

Aluminum Compression Terminal for 300 - 350 AL/CU, 266.8 18/1, 26/7, 336.4 18/1 ACSR, 350 - 400 COMPACT, 2 HOLE



*Representative Image

Features

- Connectors are prefilled with rubber compatible inhibitor and sealed with color coded end caps.

General

Color Code	None
Crimp Method	VERSAtile™ (Accommodates Conventional And Anderson Tools)
Die Size	*See Resources / Downloads for die selection and installation instructions
EU RoHS Indicator	Contact Manufacturer
Material	Aluminum
Material - Body	Aluminum
Number of Pad Holes	2
Physical Attribute - Number of Holes	2
Plating	No
Style	Impact Extruded
UPC	096359353003

Dimensions

Diameter - Pad Bolt	0.5 in
Dimension - Hole Size inch	0.500 in
Weight	0.294 lb

Conductor Related

Conductor Compatibility	ACSR-Pigeon-3/0-6/1;ACSR-Penguin-4/0-6/1;ACSR-Waxwing-266.8-18/1;ACSR-Partridge-266.8-26/7;ACSR-Ostrich-300-26/7;ACSR-Merlin-336.4-18/1;AAC-Oxlip-4/0-7;AAC-Valerian-250-19;AAC-Laurel-266.8-19;AAC-Tulip-336.1-19;AAC-Daffodil-350-19;AAAC 6201 Alloy-Amherst-195.7-6/18;AAAC 6201 Alloy-Alliance-246.9-6/18
Conductor Diameter (VersaCrimp) - Maximum	0.684 in
Conductor Diameter (VersaCrimp) - Minimum	0.475 in

Certifications and Compliance

UL Listed	No
-----------	----

Logistics

Carton Quantity	40
-----------------	----

Product Assets

[Catalogs - Distribution Connectors \(CA05127E\)](#)
[Installation Manuals - VAUL Terminals Installation Procedures](#)
[Sales Drawings - VAULxxx_drawing](#)