

HUBBELL

Power Systems

Aluminum Compression Terminal for #6 AL/CU, #4 sol CU, #6 6/1 ACSR

By ANDERSON
Catalog # [VAUL612](#)

Aluminum Compression Terminal (Replaces ESP-AD, AMS, and ALM Series)for #6 AL/CU, #4 sol CU, #6 6/1 ACSR, 1 HOLE



*Representative Image

Features

Connectors are prefilled with rubber compatible inhibitor and sealed with color coded end caps.

General

Catalog Number	VAUL612
Color Code	Blue
Crimp Method	VERSAtile™ (Accommodates Conventional And Anderson Tools)
Die Index	5/8 (243, BG)
Die Size	*See Resources / Downloads for die selection and installation instructions
EU RoHS Indicator	Contact Manufacturer
Material	Aluminum
Material - Body	Aluminum
Number of Pad Holes	1
Physical Attribute - Number of Holes	1
Plating	No
Style	Impact Extruded
UPC	096359334965

Dimensions

Diameter - Pad Bolt	0.5 in
Dimension - Hole Size inch	0.500 in
Weight	0.098 lb

Conductor Related

Conductor Compatibility	ACSR-Turkey-6-6/1;AAC-Peachbell-6-7;AAAC 6201 Alloy-Akron-30.58-6/18
Conductor Diameter (VersaCrimp) - Maximum	0.204 in
Conductor Diameter (VersaCrimp) - Minimum	0.146 in

Certifications And Compliance

UL Listed	No
-----------	----

Logistics

Carton Quantity	200
-----------------	-----

Product Assets

[Catalogs - Distribution Connectors](#)
[Installation Manuals - VAUL Terminals Installation Procedures](#)
[Sales Drawings - VAULxxx_drawing](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
AN-VAUL612-SPEC-EN | REV 6/2024