

HUBBELL

Power Systems

VERSAtile Aluminum Compression Terminal 2/0 str AL/CU; 3/8" pad bolt diameter; single hole

By ANDERSON
Catalog # [VCEL02238H1](#)



VERSAtile Aluminum Compression Terminal 2/0 str AL/CU; 3/8" pad bolt diameter; single hole

Features

CSA certified, UL Listed for both concentric and compact aluminum and concentric copper conductor

General

| | |
|-----------------------|---|
| Crimp Method | VERSAtile™ (Accommodates Conventional And Anderson Tools) |
| EU RoHS Indicator | Contact Manufacturer |
| Material | Aluminum Alloy - Tin Plated |
| Material - Body | Aluminum |
| Number of Pad Holes | 1 |
| Number of Spade Holes | 1 |
| Plating Type | Tin |
| Style | Impact Extruded |
| UPC | 096359355427 |

Dimensions

| | |
|---------------------|----------|
| Bolt Diameter | 0.38 |
| Diameter - Pad Bolt | 0.38 in |
| Weight | 0.098 lb |

Conductor Related

| | |
|---|--|
| Conductor Compatibility | ACSR-Robin-1-6/1;ACSR-Raven-1/0-6/1;AAC-Pansy-1-7;AAC-Poppy-1/0-7;AAC-Aster-2/0-7;AAAC 6201 Alloy-Azusa-123.3-6/18 |
| Conductor Diameter (Die Type Tooling) - Maximum | 0.419 in |
| Conductor Diameter (Die Type Tooling) - Minimum | 0.414 in |
| Conductor Diameter (VersaCrimp) - Maximum | 0.419 in |
| Conductor Diameter (VersaCrimp) - Minimum | 0.328 in |
| Lug Conductor Type | AL CU |

Certifications And Compliance

| | |
|-----------|-----|
| UL Listed | Yes |
|-----------|-----|

Logistics

| | |
|-----------------|-----|
| Carton Quantity | 120 |
|-----------------|-----|

Product Assets

- [Catalogs - Distribution Connectors](#)
- [Installation Manuals - VCEL installation instructions](#)
- [Sales Drawings - VCEL_drawing](#)
- [Sales Drawings - CC-11191](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
AN-VCEL02238HI-SPEC-EN | REV 6/2024