

## VERSAtile Aluminum Compression Terminal 500 MCM AL/CU; 1/2" pad bolt diameter; two hole

By ANDERSON  
Catalog # [VCEL05012H2](#)



VERSAtile Aluminum Compression Terminal 500 MCM AL/CU;  
1/2" pad bolt diameter; two hole

### Features

- CSA certified, UL Listed for both concentric and compact aluminum and concentric copper conductor

### General

Crimp Method	VERSAtile™ (Accommodates Conventional And Anderson Tools)
EU RoHS Indicator	Contact Manufacturer
Material	Aluminum Alloy - Tin Plated
Material - Body	Aluminum
Number of Pad Holes	2
Number of Spade Holes	2
Plating Type	Tin
Style	Impact Extruded
UPC	096359336501

### Dimensions

Bolt Diameter	0.5
Diameter - Pad Bolt	0.5 in
Weight	0.294 lb

### Conductor Related

Conductor Compatibility	ACSR-Quail-2/0-6/1;ACSR-Pigeon-3/0-6/1;ACSR-Penguin-4/0-6/1;ACSR-Waxwing-266.8-18/1;ACSR-Partridge-266.8-26/7;ACSR-Ostrich-300-26/7;ACSR-Merlin-336.4-18/1;ACSR-Linnet-336.4-26/7;ACSR-Oriole-336.4-30/7;ACSR-Chickadee-397.5-18/1;ACSR-Brant-397.5-24/7;ACSR-Ibis-397.5-26/7;ACSR-Lark-397.5-30/7;ACSR-Brahma-203.2-16/19;AAC-Aster-2/0-7;AAC-Phlox-3/0-7;AAC-Oxlip-4/0-7;AAC-Valerian-250-19;AAC-Laurel-266.8-19;AAC-Tulip-336.1-19;AAC-Daffodil-350-19;AAC-Canna-397.5-19;AAC-Cosmos-477-19;AAC-Syringa-477-37;AAC-Zinnia-500-19;AAC-Hyacinth-500-37;AAAC 6201 Alloy-Anaheim-155.4-6/18;AAAC 6201 Alloy-Amherst-195.7-6/18;AAAC 6201 Alloy-Alliance-246.9-6/18
Conductor Diameter (Die Type Tooling) - Maximum	0.813 in
Conductor Diameter (Die Type Tooling) - Minimum	0.811 in
Conductor Diameter (VersaCrimp) - Maximum	0.813 in
Conductor Diameter (VersaCrimp) - Minimum	0.414 in
Lug Conductor Type	<ul style="list-style-type: none"> <li>• AL</li> <li>• CU</li> </ul>

### Certifications and Compliance

UL Listed	Yes
-----------	-----

### Logistics

Carton Quantity	48
Pallet Quantity	2400

### Product Assets

[Catalogs - Distribution Connectors \(CA05127E\)](#)  
[Installation Manuals - VCEL installation instructions](#)  
[Sales Drawings - VCEL\\_drawing](#)  
[Sales Drawings - CC-11191](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
AN-VCELO5012H2-SPEC-EN | REV 1/2024