HUBBELL Power Systems

VERSAtile Copper Compression Terminal lug 500 MCM CU: 1/2" pad bolt diameter; single hole

By ANDERSON Catalog # VCELC05012H1

VERSAtile Copper Compression Terminal lug 500 MCM CU: 1/2" pad bolt diameter; single hole

*Representative Image

Features

•

VCELC05012H1

General

Catalog Number

Crimp Method

VERSAtile™ (Accomodates
Conventional And Anderson
Tools)

Inhibitor Loaded

No
Material

Copper

Material - Body

Number of Pad Holes

Number of Spade Holes

1

Holes

Plating Type Tir

Physical Attribute - Number of

Style Impact Extruded UPC 096359336594

Dimensions

Bolt Diameter 0.5 Diameter - Pad Bolt 0.5 in

Dimensions 3.400 in x 1.187 in x 0.500 in

Height 0.5 in Length 3.4 in

Length Before Compression	0 in
Weight	0.562 lb
Width	1.187 in

Conductor Related

Conductor Diameter (Die Type O.813 in Tooling) - Maximum
Conductor Diameter (Die Type O.811 in Tooling) - Minimum
Conductor Diameter O.63 in (VersaCrimp) - Maximum
Conductor Diameter O.574 in (VersaCrimp) - Minimum
Lug Conductor Type CU

Certifications And Compliance

UL Listed Yes

Logistics

Pallet Quantity 3072

Product Assets

Catalogs - Distribution Connectors Sales Drawings - VCELC_drawing Sales Drawings - CC-11191 Specifications - VCELC05012H1

