

HUBBELL

Power Systems

Tee, Aluminum Weldment

By ANDERSON

Catalog # [WTTFR3060D90](#)

Aluminum alloy weldment range taking tee for connecting aluminum tubing main to flat bar. Tongue holes have NEMA spacing. Contact surfaces on both sides of tongue. Contact sealant is recommended for pads after welding. To obtain 90 degree transverse type, add 90 to catalog number. Material: casting - 356-T6 aluminum alloy.



*Representative Image

Features

- Material: Casting - 356-T6 aluminum alloy
- Range taking tee for connecting aluminum tubing main to flat bar
- Contact surfaces on both sides of tongue
- Contact sealant is recommended for pads after welding
- To obtain 90 degree transverse type, add 90 to catalog number. Example: WTTFR06B290"

General

EU RoHS Indicator	No
Material	Aluminum
Number of Ground Braid Lug Holes	0
Number of Pad Holes	4
Type	Tee, Aluminum Weldment
UPC	096359343936

Dimensions

Angle - Pad	90 °
Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	1.568 lb
Width - Flat Bar Tap	4 in
Width - Pad	4 in

Electrical Ratings

Maximum Current Rating Amps 0
Continuous

Conductor Related

Conductor Diameter (Main) - Maximum	6.625 in
Conductor Diameter (Main) - Minimum	3.5 in
Conductor Diameter (Main) Range	3.5 - 6.625
Conductor Type	Aluminum Bus

Logistics

Pallet Quantity	324
-----------------	-----

Product Assets

[Catalogs - Substation Connectors \(SA\)](#)

[Sales Drawings - C-11289 \(WTTFR Product Family\)](#)

[Video - Hubbell Power Systems 3D Portal to help with](#)

[developing 3D models of substation connector products](#)

[Video - Hubbell Power Systems Quick Ship](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
AN-WTTFR3060D90-SPEC-EN | REV 6/2024