HUBBELL Power Systems

Bus Support, Aluminum Weldment

By ANDERSON Catalog # WURE243

Aluminum alloy, horizontal weldment bus support for tubing. Designed for slip-fit or rigid applications. Cap screws are supplied for upright mounting. Static eliminator spring furnished as standard. Material: castings - 356-T6 aluminum alloy, hardware - galvanized steel, static spring - stainless steel.



*Representative Image

Features

- Designed for rigid weldment or slip-fit without weldment
- · Static eliminator springs furnished as standard
- Four Galv-Steel HH Bolts, lock washers and flat washers provided to mount to insulator cap.

General

EU RoHS Indicator No

Material Aluminum

Material - Mounting Hardware Galvanized Steel

Number of Ground Braid Lug 0

Holes

Type Tube to Insulator UPC 096359344117

Dimensions

0 in Base Hole Spacing Diameter - Base Holes 0 in Diameter - Bolt 0 in Diameter - Bolt Circle 3 in Diameter - Inside 0 in Length - Coupling 0 in Length Before Compression 0 in Weight 2.744 lb

Electrical Ratings

Maximum Current Rating Amps 0
Continuous

Conductor Related

Conductor Type Aluminum Bus

Product Assets

Catalogs - Substation Connectors (SA)
Sales Drawings - C-11288 (WURE Product Family)
Video - Hubbell Power Systems 3D Portal to help with
developing 3D models of substation connector products
Video - Hubbell Power Systems Quick Ship

