



14x12x6 Heated & Cooled PoE Enclosure for 4 Element RPTNC External Antenna

By AccelTex Solutions
Catalog # [ATS-00247](#)



ATS-00247 (former catalog number ATS-14126P-S-L-4T-CG-POE-HC). The AccelTex Solutions Heated & Cooled PoE enclosure allows an access point to be installed in an outdoor or other temperature-limiting environment. The heater, fan and AP are all powered by a single PoE cable run from the network switch. The enclosure ships ready for an AP and external antenna installation. This version is for a 4-Element RPTNC External Antenna.

Features

- Features both heating and cooling elements to protect equipment
- Pre-configured and pre-drilled holes for 4-Element RPTNC External antennas
- Power heater, fan, and AP through a single PoE cable for outdoor applications
- The enclosure system components include:
 - 14x12x6 polycarbonate enclosure with solid door and latch lock
 - Ethernet surge suppressor for 802.3at/af/bt
 - 60W PoE Injector and Line Cord (UPOE & 802.3at/af Type 3)
 - 12VDC 15W Heater and 3" Fan
 - DC Adjustable Thermostat (Fahrenheit)
 - Ethernet Cable (For AP. Customer provides Ethernet to enclosure suppressor)
 - Ethernet Surge Suppressor pre-wired to ground
 - IP68 Rated Cord Grip
 - Blank backplate provides 10"x10.5" mounting area (Recommend 1/2" self-tap screws)
 - Vents
 - 10" DIN rail
 - Dual-Layered Fan Filter
 - 7-Port Enclosure Termination Ground Bar
 - Ground Lug Assembly with 1/4" Ring Terminal Connection Point
 - RPTNC Bulkhead Jack to Plug Lightning Arrestors (4)
 - RPTNC Jack to RPTNC Plug Cable Assemblies (4)
 - Right-Angle RPTNC Jack to RPTNC Plug Adapters (4)

Application

Indoor Wi-Fi, Outdoor Wi-Fi

General

Catalog Number	ATS-00247
Color	Grey

Compatibility

- Cisco Catalyst 9115e
- Cisco Catalyst 9120AXE
- Cisco Catalyst 9120AXP

Compatibility Hole Size

RPTNC

Cord Grip

Yes

Door Type

Solid

Enclosure Size

14x12x6

Enclosure Style

Mounting Feet

Enclosure System Components

14"x12"x6" Poly Enclosure with Solid Door, customer-provides-ethernet-to-enclosure-suppressorethernet-surge-suppressor-pre-wired-to-groundip68-rated-cord-gripblank-backplatevents10-din-raildual-layered-fan-filter7-port-enclosure-term, latch-lockethernet-surge-suppressor-for-802-3at-af-bt-type-360w-poe-injector-and-line-cord-upoe-802-3at-af-bt-type-312-vdc-15w-heater-and-3-fandc-adjustable-thermostat-fahrenheitethernHeated & Cooled
Indoor or Outdoor
Latch
Polycarbonate
4
-20 to 60 °C
802.11ac, 802.11ax, 802.11n
662620432496

Environmental Conditions

Indoor/Outdoor

Lock Type

Material

Number Of Antenna

Connection Holes

Operating Temperature

Technology


UPC

Dimensions

Dimensions	14 in x 12 in x 6 in
Height	6 in

Length14 in
Width12 in

Product Assets
[Specifications - Specification Sheet](#)



©2025 Hubbell Incorporated. All rights reserved
ATS-ATS00247-SPEC-EN | REV 4/2025