



CISCO AP SUSPENDED CEILING TILE ENCLOSURE MOUNT (9136-STYLE) ATS-CT-CISCO11-2X2



FEATURES

- Door is easily removed and can be installed to open in any direction with our innovative spring hinge system
- AP installs using the included ceiling tile grid clip shipped with the AP onto an integrated mounting plate with no tools
- Key lock for security
- Includes integrated tabs for securing enclosure mount to permanent building structure
- Shallow back box (1.5") allows installation into the tightest ceiling clearances



BENEFITS

- Easy to install
- No ceiling tile grid modification necessary (if mounting into a 2'x2' grid)
- Service the AP without removing the enclosure mount from ceiling
- Lightweight aluminum design reduces ceiling strain and load
- Simple, one person installation
- Blends seamlessly into ceiling
- No tools required for installation



MOUNT SHIPS WITH

- 2x2 Suspended Ceiling Tile Enclosure Mount with installed door
- Cord grip
- Key



MECHANICAL SPECIFICATIONS

Dimensions: 23.75" x 23.75" x 1.5" (603.25mm x 603.25mm x 38.1mm)

Weight (without AP): 3.75 lbs. (1.70 kg)

Material: Aluminum. Steel (Key & Latch Lock)

Color: White

Lock: Key Lock

Installation: Suspended Ceiling (includes tabs for securing to building structure)

Equipment Installation: AP Mounting Feet onto included Mounting Bracket

Load Capacity: 5.5 lbs. (2.5kg)



ENVIRONMENTAL SPECIFICATIONS

Installation Environment: Indoor

WARRANTY

1 Year Limited Warranty



STANDARDS, TESTING, AND CERTIFICATIONS:

- Designed to meet NEC300-22 and 300-23 to mount the Cisco AP in plenum/air handling areas UL 2416: Investigation of the enclosure system covers the enclosure only.