



# Clean Phone® VoIP Telephone, 14 Button, Surface-Mount, CE certified RoHS compliant

By Austdac  
Catalog # 116-02-0418-01W

The Clean Phone® telephone offers hands-free communications over an existing VoIP network for clean room environments. These telephones are intended for connection via RJ45 to a 10/100 BaseT Ethernet and operate using either PoE or an external dc power source. The Clean Phone® VoIP telephone features alarm reporting that enables system supervisors to monitor the telephone's activity and address maintenance issues immediately. The Clean Phone® telephone is also compatible with GAI-TRONICS' TMA (Telephone Management Application) software for maintenance monitoring from a central location. Embedded web pages permit access to each telephone, via a browser such as Internet Explorer®, to view, monitor, and change settings within the unit.

## Application

- Clean Rooms
- Clinical Environments
- Sterile Environments
- Sanitary Environments

## General

CE Compliant	CE certified RoHS compliant, Sterile Area
Catalog Number	116-02-0418-01W
Connectivity Options	VoIP
Mount location	Surface-Mount



Operating Temperature	-20° C to +60° C
Storage Temperature Range	-40° C to +70° C
Type	Keypad

## Certifications And Compliance

CE Compliant	CE certified RoHS compliant, Sterile Area
--------------	---

## Product Assets

- [Certifications - EU Declaration of Conformity \[Help Point VoIP Telephones\]](#)
- [Installation Manuals - VoIP Clean Phone® Telephones \(1193 Version\)](#)