austdac[®]

Tower with Strobe and Camera Mast

By Austdac Catalog # 234-500CAM

Free-standing tower, telephone line input; including camera mast and mast assembly kit, LED panel light, and access panel (camera and pendant housing are customer provided); 120 V ac.

Features

- Architectural Bronze color is aesthetically pleasing in all settings
- "EMERGENCY" lettering on all sides for visibility
- Custom colors and graphics available
- UL listed
- Accommodates GAI-TRONICS' LED Strobe and flush-mount emergency telephones (each sold separately)
- Includes LED Panel Light, 120 Vac
- ADA Compliant
- Wind Speed Rated @ 140 MPH* (*Reference AASHTO LTS6 Risk Category II
- International Building Code)
- Includes camera/strobe mast to accommodate customerprovided camera and pendant housing)

General

Catalog Number 234-500CAM

Compatibility GAI-TRONICS' Telephones and Strobes are Sold Separately.

Model 234 Series Tower is not compatible with RED ALERT®



surface-mount or retrofit

telephones.

Finish Type Powder-Coated Epoxy

Material Steel

Type Tower with Surveillance
Weather Rating UL/cUL listed Outdoor
Telephone Tower

Dimensions

Cubic Capacity 11400 cu.in
Depth 10 in
Height 114 in
Width 10 in

Certifications And Compliance

Certified Listed UL/cUL

Product Assets

Brochures - Red Alert Telephone Brochure

Brochures - Emergency Communications Tower Applications

(Solar/Wireless/Surveillance) Specifications - 234-500CAM

