




120 V Cellular CDMA Tower Assembly

By Austdac
Catalog # [234-500VER](#)

Free-standing tower, CDMA cellular; including lens cover kit, antenna kit, LED panel light, CDMA subpanel, battery kit; 120 V ac



Features

- Architectural Bronze color is aesthetically pleasing in all settings
- "EMERGENCY" lettering on all sides for high visibility
- Custom colors and graphics available
- UL Listed
- Accommodates GAI-TRONICS' LED Strobe and flush-mount emergency telephones (each sold separately)
- ADA Compliant
- Wind Speed Rated @ 140 MPH* (*Reference AASHTO LTS6 Risk Category II; International Building Code)

General

Catalog Number	234-500VER
Compatibility	GAI-TRONICS' Telephones and Strobes are Sold Separately. Model 234 Series Tower is not compatible with RED ALERT® surface-mount or retrofit telephones.

Finish Type	Powder-Coated Epoxy
Material	Steel
Type	Cellular Tower
Weather Rating	UL/cUL listed Outdoor Telephone Tower

Dimensions

Cubic Capacity	11400 cu.in
Depth	10 in
Height	114 in
Width	10 in

Certifications And Compliance

Certified Listed	UL/cUL
------------------	--------

Product Assets

[Brochures - Red Alert Telephone Brochure](#)
[Brochures - Emergency Communications Tower Applications \(Solar/Wireless/Surveillance\)](#)