

## Solar/Cellular GSM Tower

By Austdac  
Catalog # 234-600GSM

Free-standing tower, GSM cellular; including lens cover, solar mast, mast assembly kit, lighting kit (includes strobe), GSM & charging regulator subpanel, battery kit; 12 V dc solar power.



### Features

- Architectural Bronze and Safety Blue Standard Colors
- UL Listed
- ADA Compliant
- Durable Powder-coated Epoxy Finish
- Custom Colors and Graphics Available
- Wind Speed Rated @ 140 MPH\* (\*Reference AASHTO LTS6 Risk Category II International Building Code)
- “EMERGENCY” lettering on all sides for high visibility
- Accommodates GAI-TRONICS’ flush-mount emergency telephones (sold separately)
- Includes LED Panel Light, 10-33 Vdc

### General

Catalog Number 234-600GSM  
Compatibility GAI-TRONICS’ Telephones and Solar Panel Array sold separately. Model 234 Tower is not compatible with RED ALERT® surface-mount or retrofit telephones.

Finish Type	Powder-Coated Epoxy
Material	Steel
Type	Cellular Tower
Weather Rating	UL/cUL listed Outdoor Telephone Tower

### Dimensions

Cubic Capacity	11400 cu.in
Depth	10 in
Height	114 in
Width	10 in

### Certifications And Compliance

Certified Listed	UL/cUL
------------------	--------

### Product Assets

[Brochures - Red Alert Telephone Brochure](#)  
[Brochures - Emergency Communications Tower Applications \(Solar/Wireless/Surveillance\)](#)  
[Specifications - 234-600GSM](#)