



Solar Tower Assembly with Telephone Line

By Austdac
Catalog # [234-600TEL](#)

Free-standing tower, telephone line input; including lens cover, solar mast, mast assembly kit, lighting kit (includes strobe), charging regulator subpanel, battery kit; 12 V dc solar panel.



Features

- Architectural Bronze color is aesthetically pleasing in all settings
- "EMERGENCY" lettering on all sides for high visibility
- Custom colors and graphics available
- UL listed
- Accommodates GAI-TRONICS' flush-mount emergency telephones (sold separately)
- Accommodates 12 V dc strobe and LED panel light
- ADA Compliant
- Includes LED Panel Light, 10-33 Vdc
- Wind Speed Rated @ 140 MPH* (*Reference AASHTO LTS6 Risk Category II; International Building Code)

General

Catalog Number	234-600TEL
Compatibility	GAI-TRONICS' Telephones and Solar Panel Array sold separately. Model 234 Tower is not compatible with RED

Finish Type	ALERT® surface-mount or retrofit telephones.
Material	Powder-Coated Epoxy
Type	Steel
Weather Rating	Solar/ Phone Line Tower UL/cUL listed Outdoor Telephone Tower

Dimensions

Cubic Capacity	11400 cu.in
Depth	10 in
Height	114 in
Width	10 in

Certifications And Compliance

Certified Listed	UL/cUL
------------------	--------

Product Assets

- [Brochures - Emergency Communications Tower Applications \(Solar/Wireless/Surveillance\)](#)
- [Brochures - Red Alert Telephone Brochure](#)