austdac

Intrinsically Safe Telephone -Outdoor, Analog

By Austdac Pty Ltd Catalog # 272-001

The outdoor weatherproof telephone housing is constructed of high-impact, anti-corrosive polyester material. GAI-TRONICS' Intrinsically-Safe Telephones are the safest and most economical communication solution in hazardous environments. The Intrinsically-Safe Telephone is for use in chemical plants, refineries, grain elevators and any other environment where volatile gases and dust are a major consideration.

Features

- North American Listed for All Hazardous Groups
- cUL / UL Listed
- Replaces Explosionproof Telephones without Replacing System Cable in Most Applications
- Braille Metallic Keypad
- "Shrill"-type Penetrating Ringer
- Noise-cancelling Microphone
- Volume Control Handset
- Low Sidetone for Noisy Environments
- Switchable Power Supply 110 VAC / 220 VAC
- Hytrel® Coil Cord for Maximum Durability
- Hearing Aid Compatible (HAC)
- Extreme operating temperature range

General

Color	Gray
Connectivity Options	Analog
Mount location	Surface-Mount
Output Level Ringer	70 dBA @ 2 ft.
Signal Type	Analog
Weather Rating	Type 3R
Dimensions	

Dimensions	7.46 in x 9.39 in x 13.16 in
Height	13.16 in
Length	7.46 in
Weight	10 lb
Width	9.39 in



Electrical Ratings

Signal

Certifications and Compliance

Certification Hazardous Rating(s)

UL/CSA, FCC, IC

I.S.

- Division 1, Class I, Groups A, B, C, & D
- Division 1, Class II, Groups E, F, & G
- Division 1, Class III
- Division 2, Class I, Groups A, B, C, & D
- Division 2, Class II, Groups E, F, & G
- Division 2, Class III

Product Assets

Brochures - Rugged Telephone Brochure Installation Manuals - Intrinsically-Safe Telephones (Model 262-001 and 272-001) Literature - Intrinsically Safe Telephones

