

Clean Phone® Analog Telephone (Wall-Mount) - UL

By Austdac Catalog # 295-001W

The Clean Phone® Telephone's hands-free operation is ideal for clean room, clinical, or sanitary environments. Available in a flush-mount (295-001F) or wall-mount (295-001W) design, the Clean Phone® telephone can function in both standard or SMART operation mode. SMART (Self Monitoring And Reporting Technology) operation allows the telephone to be monitored for health and usage via our TMA software (purchased separately).

Features

- Two auto-dial numbers allow quick communication at the touch of a button.
- "Flash" button allows the Clean Phone® telephone to use features of a PBX system.
- Completely smooth front panel is sealed with an overlay that keeps the phone particulate-free and makes cleaning quick and easy.
- Auto answer option allows clean room personnel to answer calls without leaving their stations.
- Oversized buttons allow easy operation for gloved hands.
 Button function is clearly indicated.
- Password Protected Programming
- Two (2) programmable control outputs
- SMART Technology allows central health/activity monitoring via TMA software
- UL Listed

Application

- Clean Rooms
- Clinical Environments
- Sterile Environments
- Sanitary Environments

General

Catalog Number 295-001W Color Overlay

Connectivity Options Analog/SMART



Mount location Wall-Mount
Output Level Speaker 87 dB @ 1M
Signal Type Analog

Specifications UL/CSA, FCC, IC

Type Keypad Weather Rating Indoor

Dimensions

Dimensions 2.0 in x 12.0 in x 12.0 in

Height 12 in
Length 2 in
Weight 12.1 lb
Width 12 in

Electrical Ratings

Input Voltage 5 VDC
Signal Phone Line

Certifications And Compliance

Certified Listed UL/CSA, FCC, IC

Product Assets

Brochures - Healthcare Campus Communications & Controls [A HUBBCOM® Solution]

Installation Manuals - Clean Phone® Telephone (Analog)
Literature - Telephone Management Application (TMA)
Literature - Chemical List for the Clean Phone® Telephone

Literature - Clean Phone® Telephone (Analog)