austdac

Hazardous Area Analog Telephones - Outdoor - Div. 2

By Austdac Pty Ltd Catalog # 351-001

Our outdoor model 351-001, provides fully-functional, line-powered communications that are approved for use in Class I, Division 2, Groups A, B, C, D; Class II, Division 2, Groups F and G; Class III classified areas. Our outdoor models have a Type 3R weatherproof rating. Housed in corrosion-resistant enclosures, these units offer superior resistance to chemicals, solvents, salts, and extreme temperatures. Each unit is equipped with a chrome-plated zinc keypad that is fully sealed to prevent entry of dirt, contaminants, and water. The coiled handset cord on our non-metallic model is molded of thermoplastic elastomer to provide outstanding performance, memory, and long life.



- Hazardous Area approved for: Class I, Division 2, Groups A, B, C, D; Class II, Division 2, Groups F and G; Class III
- Economical Communications for Division 2 Areas
- Indoor and Outdoor Models
- Anti-corrosive Enclosures
- Hearing Aid Compatible (HAC) withPushbutton Volume Control
- Hytrel Coiled Cord or Straight Armored Cord
- · Sealed Chrome-plated Keypad
- Extreme Operating Temperature Range
- Conformal Coating on PCBA

General

Color Blue
Connectivity Options Analog
Mount location Surface-Mount
Output Level Ringer 84 @ 1M
Signal Type Analog
Type Outdoor Use
Weather Rating Type 3R

Dimensions

Dimensions 7.4 in x 13.2 in x 9.4 in

Height 9.4 in
Length 7.4 in
Weight 8.2 lb
Width 13.2 in



Electrical Ratings

Signal Phone Line

Certifications and Compliance

Certification • UL

• CSA

IC

Hazardous Rating(s) • Class I, Division 2, Groups

A, B, C, D

• Class II, Division 2, Groups

F & G

• Class III, Division 2

Nema Rating NEMA 3R

Product Assets

Brochures - Rugged Telephone Brochure Installation Manuals - Model 226-002, 341-001, and 351-001 Div. 2 Industrial Telephones Literature - Hazardous Area Telephones

Related Products

230-001 - Pole Mounting Kit (for 25x, 351, 354, XB001)

