



SP2 PoE / PoE+ Indoor Handset Stations; 915-A21R100

By Austdac Pty Ltd
Catalog # [915-A21R100](#)

SP2 with Power over Ethernet (PoE/PoE+) operation is one of GAI-TRONICS' most advanced paging and intercom systems. Combining the simplicity of "press to page, release to party" operation with cutting-edge multicast Voice over Internet Protocol (VoIP) technology, SP2 is capable of providing virtually instant communication in the most demanding of environment.

Features

- Multicast VoIP Technology
- Serverless Technology
- Full Duplex Communication
- Five Party Lines
- PoE or PoE+ Operation
- Efficient Class D Amplifier with up to 14W Output
- Ambient Level Sensing (ALS)
- Remote Terminal Unit (RTU) Operation for Input/Output Applications
- Remote Monitoring
- CAT5/5E Network Connection
- Indoor Mounting

General

Color	Safety Orange
Connectivity Options	VoIP, Ethernet with RTU
Construction	16-gauge Cold-rolled Steel
Finish Type	Safety orange powder coating
Material	ABS
Output Level Speaker	8 ohm
Power	14 Watt (PoE+)
Series	SP2
Temperature Range	-22° F to +140° F (-30° C to +60° C)
Weather Rating	NEMA Type 12



Dimensions

Cubic Capacity	481.6875 cu.in
Depth	7.34
Height	12.5 in
Width	5.25 in

Certifications and Compliance

Certified Listed	<ul style="list-style-type: none">• CAN/CSA-C22.2 No. 60950-00• UL 60950
Hazardous Rating(s)	UL Safe Area

Product Assets

[Brochures - SP2 - VoIP Multicast Paging & Intercom Brochure](#)
[Configuration Guide - SP2 Configuration Guide](#)
[Installation Manuals - SP2 Configuration Guide](#)
[Installation Manuals - SP2 POE Handset/Speaker Amplifier Station](#)
[Literature - SP2 PoE/PoE+ Indoor Handset Stations](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
AUST-915-A21R100-SPEC-EN | REV 7/2023