

1PLD2/08, UV Rated Black, 2sided, 8-port, #14-2/0 AWG

By Burndy Catalog # 1PLD2/08






- UV Rated Covering over AL6061-T6 aluminum body saves time, lowering installation costs and eliminates taping
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces the number of connectors necessary to carry in inventory

General

Catalog Number	1PLD2/08
Connector Type	Multi Tap
Hex Key	3/16
Installation Torque Recommended in-Ib	120 in-lb
Insulation	Υ
Insulation Type	Plastisol
Material	Aluminum
Material - Hardware	Aluminum
Number Of Ports	8
Physical Attribute - Number of Screws	8
Physical Attribute - Screw Type	Allen
Plated	Ν
Plating Type	Unplated
Temperature Rating	194° F
Trade Name	UNITAP™
UPC	781810308332
UPC 12 Digit	7818103083322
Dimensions	

Dimensions

Dimension - Height fraction	1.375 in
Dimension - Height inch	1.38 in
Dimension - L Length Overall	141 mm
mm	
Dimension - Length Overall inch	5.55 in
Dimension - Screw Size inch	7/16
Dimension - Width inch	1.56 in
Dimension - Width mm	40 mm



Electrical	Ratings
LICCUICAI	Raungs

Voltage - Maximum	600 V
Conductor Related	
Conductor - AL Str Size	14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG
Conductor - AL Str Size Range	14 AWG - 2/0 AWG
Conductor - Copper Str Size	14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG
Conductor - Copper Str Size Range	14 AWG - 2/0 AWG
Conductor Size	14-2/0 AWG
Conductor Type	AL C Str-Size
	CU C Str-Size

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	СМ
UL Listed	Yes

Logistics

Minimum Pack Quantity

Product Assets

Catalogs - UNITAP[™] Products Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Product Cross Section Image(s) - BUR_1PLD2010_LineArt Sales Drawings - 10013354

1

