

1PLM2/010, UV Rated Black, Mount Tap, 1-side, 10-port

By Burndy Catalog # 1PLM2/010

Mounted Block Tap Connector, 10 Ports, Single Side Entry, 7.98 IN L



Features

- UV Rated Covering over AL6061-T6 aluminum body saves time, lowering installation costs and eliminates taping
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces the number of connectors necessary to carry in inventory

General

Catalog Number 1PLM2/010
Connector Type Multi Tap
Installation Torque 275 in-lb

Recommended in-lb

Insulation Y
Insulation Type Plastisol
Material Aluminum

Number Of Ports 10 Physical Attribute - Number of 12

Screws

Plated Y

Plating Type Clear Plated
Temperature Rating 194° F
Trade Name UNITAP™
UPC 781810307847
UPC 12 Digit 7818103078477

Dimensions

Dimension - Height fraction 1-1/2 in
Dimension - Height inch 1.50 in
Dimension - L Length Overall 203 mm

mm

Dimension - Length Overall 7.98 in

inch

Dimension - Width inch 1.44
Dimension - Width mm 36 mm

Electrical Ratings

Voltage - Maximum 600 V

Conductor Related

Conductor - AL Str Size 14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5

AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG

Conductor - AL Str Size 14 AWG - 2/0 AWG

Range

Conductor - Copper Str Size 14 AWG;12 AWG;10 AWG;9

AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG

Conductor - Copper Str Size

Range

Conductor Size Conductor Type 14-2/0 AWG

AL C Str-SizeCU C Str-Size

14 AWG - 2/0 AWG

Certifications And Compliance

Certification - CSA Approved Yes
Certification - ETL No
Certification - UL Listed Direct No
Burial
Certification - UL Recognized No
Certification - cULus No
Standards - RoHS Compliance Status

UL Listed Yes

Logistics

Minimum Pack Quantity 1

Product Assets

Catalogs - UNITAP™ Products Catalogs - Full Line BURNDY Catalog

Product Cross Section Image(s) - BUR_PLM_LineArt

Sales Drawings - 50015718

