

1PLMD2/06, UV Rated Black, Mount Tap, 2-sided, 6-port

By Burndy Catalog # 1PLMD2/06

Mounted Block Tap Connector, Single Side Entry, 5.29 IN L.



Features

- UV Rated Covering over AL6061-T6 aluminum body saves time, lowering installation costs and eliminates taping
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces the number of connectors necessary to carry in inventory

General

Catalog Number	1PLMD2/06
Connector Type	Multi Tap
Installation Torque Recommended in-Ib	120 in-lb
Insulation	Υ
Insulation Type	Plastisol
Material	Aluminum
Material - Hardware	Aluminum
Number Of Ports	6
Physical Attribute - Number of Screws	8
Plated	Υ
Plating Type	Clear Plated
Temperature Rating	194° F
Trade Name	UNITAP™
UPC	781810307533
UPC 12 Digit	7818103075333

Dimensions

Dimension - Height fraction	1-1/2 in
Dimension - Height inch	1.5
Dimension - L Length Overall	134
mm	
Dimension - Length Overall inch	5.29
Dimension - Width inch	1.56
Dimension - Width mm	40 mm

600 V

Electrical Ratings

Voltage - Maximum

Conductor Related

Conductor - AL Str Size	14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG
Conductor - AL Str Size Range	14 AWG - 2/0 AWG
Conductor - Copper Str Size	14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG
Conductor - Copper Str Size Range	14 AWG - 2/0 AWG
Conductor Size	14-2/0 AWG
Conductor Type	AL C Str-Size
	CU C Str-Size

Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Listed Direct Burial	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	СМ
UL Listed	Yes

Logistics

Minimum Pack Quantity

Product Assets

Catalogs - UNITAP™ Products Catalogs - Full Line BURNDY Catalog Product Cross Section Image(s) - BUR_PLM_LineArt Sales Drawings - 50015715

1

