

ACC-ECTA1211, Vertical 90 Degree Edge Clip with Nylon12 Cable Tie, 11"

By Burndy Catalog # ACC-ECTA1211


Wiley Edge Clip with Cable Tie, Vertical (90 deg.) parallel installation

Features

- Route cable bundles without the need for mounting holes or additional hardware
- Installs in a vertical/parallel (90°) or horizontal/perpendicular (180°) orientation
- Steel lances securely anchor clips to module frames or purlins
- Offered in various nylon types with 50 lb tensile strength:UV resistant, high impact heat stabilized Nylon 6/6
 UV resistant Nylon 12 which provides excellent UV, chemical and moisture resistance

Application

- For routing cable bundles without requiring mounting holes or additional hardware, Available in Nylon 6/6 or Nylon 12 for either horizontal/perpendicular (90°) or vertical/ parallel (180°) styles
- 50 lb tensile strength, Steel lances securely anchor clips to module frames / purlins, 3 standard cable tie lengths (8", 11", 14") encompass maximum bundle diameters of 1.95" to 3.94"
- Custom lengths available



General

| Catalog Number | ACC-ECTA1211 |
|-------------------|--|
| Installation Type | Vertical (90 deg.) parallel installation |
| Material | Nylon 12 |
| Tensile Strength | 50 lb. |
| UPC | 621945554351 |

Dimensions

| Dimension - Bundle Diameter | 2.95 in |
|-----------------------------|---------|
| Max inch | |
| Length | 11 in |

Certifications And Compliance

| Certification - CSA Approved | Ν |
|------------------------------|--------------------|
| Certification - cULus | Ν |
| Certified Listed | UL62275 Recognized |
| Industry Standard(s) | UL62275 Recognized |

Logistics

Carton Quantity 1000

Product Assets

Catalogs - Wiley_WireManagementSolutions_Cat Catalogs - Section E4 - Wiley Grounding Catalogs - Section G - Wire Management Certifications - UL Certificate of Compliance UL 62275 Sales Drawings - 50100741

