

B2F12N Flexible Copper Braid

By Burndy Catalog # B2F12N

Flexible Cu Braid Jumper, 12" L, Amp Rating: 600(Indoor), 720(Outdoor).



Dimension - N inch	0.62 in
Dimension - Pad Width inch	1.38 in
Length	12 in

Electrical Ratings

Rating - Indoor Amperage	600
Rating - Outdoor Amperage	720

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards	UL467
Met	
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes

Logistics

Minimum Pack Quantity 1

Product Assets

Catalogs - BURNDY Master Catalog - Section E2 - Mechanical Grounding
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice
Interactive Catalog - BURNDY Full-Line Digital Catalog
Product Cross Section Image(s) - BUR_BD_Lineart
Sales Drawings - SE..212512-01
Specifications - B2F12N

Features

- Most Burndy braid are UL Listed and CSA Certified
- Pressed seamless copper ferrules provide added durability and prevent fraying, providing extra strength for a robust bonding connection
- Braid is especially suited for applications that require flexibility or resistance to vibration
- Extra fine stranding gives enhanced flexibility
- Ferrules clearly marked with Burndy braid type and UL markings (where appropriate)
- Available in custom lengths and hole sizes to suit your needs (contact your local sales representative for non-standard configurations)
- For assistance in finding the perfect braid for your needs click here for our Braid Configurator Tool: www.hubbell.com/config/BRAID

General

Catalog NumberB2F12NConnector TypeBraidMaterialCopperMaterial - FerrulesYPhysical Attribute - Number of2

Braids

Plated

UPC 781810809129

Dimensions

Dimension - D inch

Dimension - Hole Size inch

Dimension - L Length Overall

3.00 in

0.56 in

305 mm

mm

Dimension - Length Overall 12.00 in

inch