

BA14E516, Vinyl Ring Terminal For 16 - 14 AWG

By Burndy Catalog # BA14E516



Vinyl Ring Terminal For 16 - 14 AWG.

Features

- Expanded insulation support accepts standard and large wire diameters providing lower inventory requirements and greater flexibility
- Funnel entry for easy wire insertion
- Manufactured of pure electrolytic copper to provide maximum conductivity, low resistance and ductility for excellent crimp forming properties
- Deep V groove serration in the inner barrel for added holding strength and better conductivity
- Electro-tin plating for durable, long-lasting corrosion resistance
- 600 Volts maximum, 105°C maximum

General

Catalog Number	BA14E516
Connector Type	Ring Terminal
Feature - Barrel Style	Shrouded
Insulation	Y
Insulation Type	Vinyl
Material	Copper
Physical Attribute - Number of	1
Holes	
Physical Attribute - Tongue	Ring
Туре	
Plated	Y
Plating Type	Tin - Electroplated
Trade Name	VINYLUG™
Туре	Ring Tongue
UPC	781810082195

Dimensions

Dimension - Bolt Size fraction	5/16
Dimension - Hole Size fraction	8/25 in
Dimension - Hole Size inch	0.32 in
Dimension - Length Overall	1.15 in
inch	

Dimension - Pad Width inch	0.53 in
Dimension - Stud Size inch	5/16 in
Dimension - Z (inch)	0.45 in

Conductor Related

Conductor - Copper Solid Size	16 AWG;15 AWG;14 AWG
Conductor - Copper Solid Size	16 AWG-14 AWG
Range	
Conductor - Copper Str Size	16 AWG; 14 AWG
Conductor - Copper Str Size	16 AWG - 14 AWG
Range	
Conductor Size	16 - 14 AWG
Conductor Type	CU C Str-Size

Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Standards - Industry Standards	UL486
Met	
Standards - RoHS Compliance	СМ
Status	
UL Listed	Yes

Logistics

Carton Quantity	1000
Minimum Pack Quantity	1000
Pallet Quantity	99999

Product Assets

Catalogs - BURNDY Master Catalog - Section B - Small Compression Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Sales Drawings - 50093722 Specifications - BA14E516

