



BCSC146900, Black Cold Shrink Sleeve, 9" Length, Jacket OD Range: .70"-1.05"

By Burndy
Catalog # [BCSC146900](#)



Black Cold Shrink, Specially formulated silicone rubber offering excellent insulation and moisture resistant sealing for in-line cable connector systems. The rubber sleeves are factory expanded over a removeable, plastic ripcord housing. Installs quickly and easily with no heat gun or other installation tools. Passes TELCORDIA GR-347-CORE Abrasion and Cut Test up to 750 kcmil. Operating temperature range: -40°C to +105°C.

Features

- Length of tube is consistent before and after application
- Easy, safe installation
- Suitable for wide range of cable sizes
- UV resistance, thermal stability
- No special tools or training required
- Forms a moisture resistant seal
- Indoor and outdoor applications
- Rip and Grip Installation does not require heat gun or any installation tools
- Passes TELCORDIA GR-347-CORE Abrasion and Cut Test up to 750 kcmil
- cUL insulating cover for wire connectors tested in accordance to UL 486A/B
- Passes UL 746C Glow Wire Test
- Ripcord is recyclable

Application

Cold Shrink, Rated to 2000 Volts, offer insulation and moisture resistant sealing for in-line cable connector systems

General

| | |
|----------------|-----------------|
| Catalog Number | BCSC146900 |
| Color | Black |
| Material | Silicone Rubber |
| UPC | 621945667969 |

Dimensions

| | |
|--------|------|
| Length | 9 in |
|--------|------|

Electrical Ratings

| | |
|----------------|--------|
| Voltage Rating | 2000 V |
|----------------|--------|

Logistics

| | |
|-----------------|-----|
| Carton Quantity | 162 |
|-----------------|-----|

Product Assets

[Catalog Page - BURNDY Page D2 & D3 - Cold Shrink Catalogs](#) - [BURNDY Master Catalog - Section D - Shrink Tubing Catalogs](#) - [BURNDY Master Catalog - Full Line BURNDY Catalog Interactive Catalog](#) - [BURNDY Full-Line Digital Catalog Sell Sheets - Clear & Black Cold Shrink - Rated for 2000 Volts Specifications](#) - [BCSC146900](#)