

# BIBD2/02FX, Double Sided Flex Rated Two Conductor Clear Insulated Mult-Tap Connector

By Burndy Catalog # BIBD2/02FX



### **Features**

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory
- · Suitable for Code and Flex Conductor
- Color-coordinated conductor port caps display wire range and classes of conductor accepted
- Screw port caps show installation torque information for easy reference

#### **Application**

Tap connections and in-line splice/reductions are made quickly and easily with the UNITAP $^{\text{TM}}$  line of connectors

## General

Catalog Number BIBD2/02FX
Connector Type Multi Tap
EU RoHS Indicator Yes
Insulation Y

Material Aluminum
Plated N

Plating Type Unplated
Sub Brand UNITAP
Temperature Rating 194
Trade Name UNITAP™

Type BIBD, Multi-Port UPC 621945438774 UPC 12 Digit 6219454387744



#### **Dimensions**

Dimension - Height mm 0 mm

**Electrical Ratings** 

Voltage - Maximum 600 V

#### **Conductor Related**

Conductor Size 14-2/0 AWG
Conductor Type • AL C Str-Size
• CU C Str-Size

#### **Certifications And Compliance**

Buy American Compliant Under Review

Certification - CSA Approved Ye

Industry Standard(s) UL 486A-486B Standards - Industry Standards UL 486A-486B

Met

Standards - RoHS Compliance CM

Status

UL Listed Yes

## Logistics

Minimum Pack Quantity 1

#### **Product Assets**

Catalogs - UNITAP™ Products

Catalogs - BURNDY Master Catalog - Section A - Mechanical

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Sales Drawings - 50046931 Specifications - BIBD2/02FX

Specifications - Burndy\_BIBD202FX\_Specsheet

