

BIBD25012FX, Double Sided Flex Rated Twelve Conductor Clear Insulated Mult-Tap Connector

By Burndy Catalog # BIBD25012FX

Aluminum UNITAP, Double Sided Entry, #10-250 Class B & C ,#10-3/0 Class G,H,I,K, DLO, 12 PORT.

Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory
- Suitable for Code and Flex Conductor
- Color-coordinated conductor port caps display wire range and classes of conductor accepted
- Screw port caps show installation torque information for easy reference

General

Catalog Number BIBD25012FX
Connector Type Multi Tap
Insulation Y
Material Aluminum
Plated N
Plating Type Unplated
Temperature Rating 194

 Trade Name
 UNITAP™

 UPC
 621945438965

 UPC 12 Digit
 6219454389655

Electrical Ratings



Voltage - Maximum 600 V

Conductor Related

Conductor Size 10 AWG-250 KCMIL

Conductor Type • AL C Str-Size

• CU C Str-Size

Certifications And Compliance

Certification - CSA Approved Yes

Industry Standard(s) UL 486A-486B Standards - Industry Standards UL 486A-486B

Met

Standards - RoHS Compliance CM

Status

UL Listed Yes

Logistics

Minimum Pack Quantity 5

Product Assets

Catalogs - UNITAP™ Products

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section A - Mechanical Interactive Catalog - BURNDY Full-Line Digital Catalog

Sales Drawings - 50046931 Specifications - BIBD25012FX

