

BIBD3508FX, Double Sided Flex Rated Eight Conductor Clear Insulated Mult-Tap Connector

By Burndy Catalog # BIBD3508FX

Aluminum UNITAP, Double Sided Entry, #10-350 Class B & C ,#10-250 Class G,H,I,K, DLO, 8 PORT.

Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory
- · Suitable for Code and Flex Conductor
- Color-coordinated conductor port caps display wire range and classes of conductor accepted
- Screw port caps show installation torque information for easy reference

General

Catalog Number BIBD3508FX
Connector Type Multi Tap

Insulation Y

Material Aluminum

Number Of Ports8PlatedYPlating TypeTin

Temperature Rating -40° C to 135 °C Trade Name UNITAP™ UPC 621945438699 UPC 12 Digit 6219454386999

Dimensions

Dimension - Length Overall 7.430 in

inch



Electrical Ratings

Amperage Rating 310 A Voltage - Maximum 600 V

Conductor Related

Conductor - AL Str Size Range 10AWG-250 kcmil
Conductor Size 10 AWG-350 KCMIL
Conductor Type • AL C Str-Size
• CU C Str-Size

Certifications And Compliance

Certification - CSA Approved Ye

Industry Standard(s) UL 486A-486B Standards - Industry Standards UL 486A-486B

Met

Standards - RoHS Compliance CM

Status

UL Listed Yes

Logistics

Minimum Pack Quantity 1

Product Assets

Catalogs - UNITAP™ Products

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Catalogs - BURNDY Master Catalog - Section A - Mechanical

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Sales Drawings - 50046931 Specifications - BIBD3508FX

