

BIBS3504MT, Single Sided Mounted Four Conductor Clear Insulated Mult-Tap Connector

By Burndy Catalog # BIBS3504MT

Aluminum Multiple Tap Connector w/ Mount Holes, Clear Insulated, 4 Port, 1 Sided Entry, 10 AWG-350 kcmil, Al/Cu Rated.



- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

BIBS3504MT

General

Catalog Number

Connector Type Multi Tap Hex Key 5/16 Insulation Plastisol Insulation Type Material Aluminum Number Of Ports Physical Attribute - Number of Physical Attribute - Screw Type Allen Plated Unplated Plating Type Temperature Rating 194 UNITAP™ Trade Name UPC 781810253113 UPC 12 Digit 7818102531133

Dimensions

Dimension - Height inch

Dimension - Height mm

Dimension - Length Overall

Dimension - Length Overall

Dimension - Length Overall

Dimension - Width inch

Dimension - Width mm

2.63 in

149 mm

5.86 in

2.19 in

Dimension - Width mm



Electrical Ratings

Voltage - Maximum 600 V

Conductor Related

Conductor - AL Str Size Range
Conductor - Copper Str Size
Range
Conductor Size
Conductor Type

10 AWG - 350 kcmil

Certifications And Compliance

Certification - CSA Approved Yes Certification - ETL No Certification - UL Listed Direct No Burial Certification - UL Recognized Nο Certification - cULus No UL467 Industry Standard(s) Standards - Industry Standards UL467 Standards - RoHS Compliance СМ Status **UL** Listed Yes

Logistics

Minimum Pack Quantity 5

Product Assets

Catalogs - BURNDY Master Catalog - Section A - Mechanical
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice
Interactive Catalog - BURNDY Full-Line Digital Catalog
Product Cross Section Image(s) - BUR_BIBS-MT_LineArt
Sales Drawings - 213079
Specifications - BIBS3504MT

