

# BIBS3505, Single Sided Five Conductor Clear Insulated Multi-Tap Connector

By Burndy Catalog # BIBS3505

MULTI-PORT Single-Sided Entry.



### **Features**

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

### General

Connector Type Multi Tap Hex Key 5/16 Insulation Insulation Type Plastisol Material Aluminum Number Of Ports Physical Attribute - Number of 10 Screws Physical Attribute - Screw Allen Type Plated Plating Type Unplated Temperature Rating 194 Trade Name UNITAP™ UPC 781810133507 UPC 12 Digit 7818101335077 **Dimensions** 

Dimension - Height inch

Dimension - L Length Overall

mm

Dimension - Length Overall

inch

Dimension - Width inch

Dimension - Width mm

2.30 in

2.4.95 in

2.32 in

2.32 in

## **Electrical Ratings**

Voltage - Maximum 600 V

#### **Conductor Related**

Conductor - AL Str Size
Range
Conductor - Copper Str Size
Range
Conductor Size
Conductor Type

10 AWG - 350 kcmil
10 AWG - 350

## **Certifications And Compliance**

Certification - CSA Approved Certification - ETL Certification - UL Listed Direct No Burial Certification - UL Recognized Nο Certification - cULus Industry Standard(s) UL 486A-486B Standards - Industry UL 486A-486B Standards Met Standards - RoHS Compliance Status **UL** Listed Yes Logistics Minimum Pack Quantity

## **Product Assets**

3D Models - BIBS3505\_MODEL-IGES
3D Models - BIBS3505\_MODEL-PDF
3D Models - BIBS3505\_MODEL-STEP
Catalogs - UNITAP™ Products
Catalogs - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice
Product Cross Section Image(s) - BUR\_BIBS\_Lineart
Sales Drawings - sc210991-13

